


Product Data Sheet












Z Polyester Cloth

RG998

Ideal for heavy deburring and sanding cast iron, high alloy steel, heat resistant steel, low alloy steel, stainless steel, aluminum, zamak and cast iron materials in wide belts, narrow belts and rolls. Z polyester cloth backing with close coated 100% Ceramic abrasive, also with friction and heat resistant Topsize coating. Suitable for wet applications.

Product Code	Abrasive Grain	Backing	Coating	Jumbo Width (mm)	Grit Range
RG998	100% Ceramic	Z Polyester Cloth	Topsize & Closed	1410	24 - 120

Grit Range															
24	36	40	50	60	80	100	120								

Product Forms				
 Jumbo	 Segmented Belt (Multi Joint)	 Wide Belt	 Narrow Belt	 Roll
 Disc	 Velcro Disc	 Flap Wheel	 Flap Disc	

Application Areas			
Wood	Parquet / Floor Sanding	Low Alloy Steel	Stainless Steel / Inox
High Alloy Steel / Heat Resistant Steel	Aluminium / Zamak	Brass / Copper / Non Ferrous Metals	Paint / Varnish / Lacquer
Plastic / Rubber / Leather	Cast Iron	Glass / Stone / Granite / Ceramic	

Features		
Antistatic Feature	Suitable for Wet Applications	Friction & Heat Absorbant (Top Size)
Anti-Clogging (Stearate)	Flexible for Curved Surfaces	Tear Resistant