
J Flexible Polycotton Cloth

RC781

Ideal for sanding brass, copper, non-ferrous steel, aluminum, zamak, plastic, rubber, leather, glass, stone, granite, ceramic, wood, low alloy steel and stainless steel materials in narrow belt sand rolls. Light weight J flexible poly-cotton cloth backing with Silicon Carbide abrasive. Flexible structure, ideal for polishing hardware sanitary.



| Product Code | Abrasive Grain | Backing | Coating | Jumbo Width (mm) | Grit Range | | | | |
|--------------|-----------------|--------------------------------|---------|------------------|------------|--|--|--|--|
| RC781 | Silicon Carbide | J Flexible Polycotton Cloth | Closed | 1400 | 60 - 1000 | | | | |
| Crit Page | | | | | | | | | |

| | | | | | | | Grit H | cange | | | | | | | | |
|--|--|----|----|-----|-----|-----|--------|-------|-----|-----|-----|-----|-----|-----|------|--|
| | | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 400 | 500 | 600 | 800 | 1000 | |

| | Product Forms | | | | | | | | |
|-------|------------------------------|------------|-------------|------|--|--|--|--|--|
| | | | | | | | | | |
| Jumbo | Segmented Belt (Multi Joint) | Wide Belt | Narrow Belt | Roll | | | | | |
| | | | | | | | | | |
| | Velcro Disc | Flap Wheel | Flap Disc | | | | | | |

| Application Areas | | | | | | | | |
|---|-------------------------|-------------------------------------|---------------------------|--|--|--|--|--|
| Wood | Parquet / Floor Sanding | Low Alloy Steel | Stainless Steel / Inox | | | | | |
| High Alloy Steel / Heat Resistant Steel | Aluminium / Zamak | Brass / Copper / Non Ferrous Metals | Paint / Varnish / Lacquer | | | | | |
| Plastic / Rubber / Leather | Cast Iron | Glass / Stone / Granite / Ceramic | | | | | | |

| | Features | |
|--------------------------|-------------------------------|--------------------------------------|
| | Suitable for Wet Applications | Friction & Heat Absorbant (Top Size) |
| Anti-Clogging (Stearate) | Flexible for Curved Surfaces | Tear Resistant |

